


# SafeSite® LED High Bay

## Ordering Information



### Product Code<sup>3</sup>

<b>HE</b>	High Bay 3/4" NPT
HC	Integrated Pendant Wiring Box
HW	Integrated Hexagon Wiring Box

### Certification

C	UL844, CID1
<b>D</b>	UL 844 CID2, CIID2, CIID1, CIID
M	UL 844 CID1 + Paint Spray Listed
H	UL 844 CID1 + Group B Hydrogen

\*HCD & HWD models not available with Class II, Div. 1 Groups E, F and G. Use HED or HEC models.

### Lens Material

4	Polycarbonate - Clear
5	Polycarbonate - Diffused
<b>7</b>	Glass - Clear
8	Glass - Diffused
L	Polycarbonate Dome - Diffused

\*All lens options flat except L

### Beam Distribution

E	Oval
<b>M</b>	Medium
N	Narrow
W	Wide

### CCT & CRI

<b>C</b>	Cool White 5000K - 80 CRI
N	Neutral White 4000K - 80 CRI
W	Warm White 2700K - 80 CRI

### Operating Voltage

<b>2</b>	100-277 VAC / 120-250 VDC
A <sup>1</sup>	347-480 VAC (HE, HEC & HEW only)
P	480 VAC (HE passive only)
Q	347 VAC (HE passive only)

### Lumen Type (HED, HCD & HWD)<sup>2</sup>

A	11,000 Lumens
B	14,000 Lumens
C	18,000 Lumens
<b>E</b>	27,000 Lumens

### Lumen Type (HEC, HEM, HEP)<sup>2</sup>

A	13,500 Lumens
B	16,500 Lumens
C	19,500 Lumens
E	29,500 Lumens

### Controls

D <sup>4</sup>	Dimming (0-10 VDC)
<b>N</b>	Non Dimming

### Mounting Options

H	Hook
<b>N</b>	Pendant 3/4" NPT
P	Pendant 3/4" NPT Safety Retention Tabs
Q	Safety Retention Tabs with HBXW3
R	Hook with Safety Retention Tabs

### Power Cable

N	No power cable (HC & HW models only)
T	1.5' [0,5 meter] Power Cable
U	3' [1 meter] Power Cable
V	6' [1,8 meter] Power Cable
<b>W</b>	10' [3 meter] Power Cable

### Electrical Accessories

<b>N</b>	No Option
----------	-----------


### Coatings

<b>G</b>	Gray (RAL 7040)
----------	-----------------

### Notes

- 347/480 VAC options only available on CID2, CIID2, CIID1 models with Product Code prefix HE. 347/480 VAC models come with wiring box & transformers. For 480 VAC add 12W, for 347 VAC add 29W.
- Lumen type based on glass lens, when using alternative lenses use table on page 59.
- For CID1 models use Product Code prefix HE or HW (glass), HC is not valid. For lens, only option 7 (glass) is available for CID1 models.
- Passive voltage options P & Q are not available with dimming.

Additional features and selections are available, please see the UL High Bay Technical Spec Sheet or your Dialight representative for more information.



When ordering please refer our website [www.dialight.com](http://www.dialight.com) to view the current versions of all relevant product documentation, including the most up to date product data sheets. For the avoidance of doubt, in the event of any discrepancy between the contents of this document and information provided on our website, the information provided on our website shall prevail.